MICROLITRBO









Prominently used for Molecular Biology, Microbiology, Immunology, Cell Culture, Analytical Chemistry, Biochemistry, Genetics.





Adjust Volume Easily with Plunger

The Plunger has been carefully designed with a high quality spring mechanism to ensure snag free and soft movement. Simply turn it to adjust the instrument's volume comfortably.



Use Various Tips with a Universal Tipcone

A Universal Tipcone enhances the compatibility of the instrument and enables it to easily work with most of the internationally accepted standard tips.



Set the Volume with Perfection

A soft click sound at every increment ensures perfect volume setting and prevents any accidental changes. It also facilitates singlehanded operation.



Store Safely with a Holder

The Instrument includes a Holder that enables easy, efficient and safe storage.



Eject Tips Easily with a Tip Ejector

An in-built, streamlined Tip Ejector enables easy tip ejection and comfortable access to bottles and tubes with narrow necks.



Work with a Good Grip

A specially designed large Grippy provides good grip and great ease of use while operating.

The Single Channel Variable Volume Micropipette is available in 9 unique volume ranges from 0.2 µl to 10 ml.

z	Model	Volume	Inc.	А		CV	
MATIC	Model	Range	μl	±%	±μΙ	±%	±μΙ
FORI	RBO-2	0.2-2.0 µl	0.002	2	0.04	1.2	0.024
SPECIFICATIONS AND ORDERING INFORMATION	RBO-10	0.5-10 µl	0.02	1	0.1	0.5	0.05
	RBO-20	2-20 µl	0.02	0.8	0.16	0.4	0.08
	RBO-50	5-50 μΙ	0.1	0.8	0.4	0.4	0.2
	RBO-100	10-100 µl	0.2	0.6	0.6	0.2	0.2
	RBO-200	20-200 μΙ	0.2	0.6	1.2	0.2	0.4
	RBO-1000	100-1000 µl	1.0	0.6	6	0.2	2
	RBO-5000	0.5-5 ml	10.0	0.6	30	0.2	10
SP	RBO-10000	1-10 ml	20.0	0.6	60	0.2	20

Single Channel Fixed Volume Micropipette

The instrument is fully autoclavable at 121 °C and 15 psi for a duration of 10 -15 minutes

Recommended for Clinical Diagnostics, Control Analysis.





Use Various Tips with a Universal Tipcone

A Universal Tipcone enhances the compatibility of the instrument and enables it to easily work with most of the internationally accepted standard tips.



Work with a Good Grip

A specially designed large Grippy provides good grip and great ease of use while operating.



Store Safely with a Holder

The Instrument includes a Holder that enables easy, efficient and safe storage.



Eject Tips Easily with a Tip Ejector

An in-built, streamlined Tip Ejector enables easy tip ejection and comfortable access to bottles and tubes with narrow necks.

The Single Channel Fixed Volume is available in 15 unique volumes from 1.0 µl to 10 ml.

_	Model	Vol.	<i>A</i>	Α		.V
ē	Wiodei	μl	±%	±μΙ	±%	±μΙ
¥	RBO-F-1	1.0	5	0.05	5	0.05
N.	RBO-F-2	2.0	4	0.08	2	0.04
Ř	RBO-F-5	5.0	2	0.1	1	0.05
= ບ	RBO-F-10	10.0	1	0.1	0.5	0.05
Z Z	RBO-F-20	20.0	0.8	0.16	0.4	0.08
SPECIFICATIONS AND ORDERING INFORMATION	RBO-F-25	25.0	0.8	0.2	0.4	0.1
	RBO-F-50	50.0	0.8	0.4	0.4	0.2
	RBO-F-100	100.0	0.6	0.6	0.2	0.2
	RBO-F-200	200.0	0.6	1.2	0.2	0.4
SNS	RBO-F-250	250.0	0.6	1.5	0.2	0.5
Ĭ	RBO-F-500	500.0	0.6	3	0.2	1
<u>S</u>	RBO-F-1000	1000.0	0.6	6	0.2	2
늉	RBO-F-2000	2000.0	0.6	12	0.2	4
Ä	RBO-F-5000	5000.0	0.6	30	0.2	10
0)	RBO-F-10000	10000.0	0.4	40	0.2	20

Recommended for ELISA (Diagnostic Test), Molecular Screening, Kinetic Studies, DNA Amplification





Adjust Volume Easily with Plunger

The Plunger has been carefully designed with a high quality spring mechanism to ensure snag free and soft movement. Simply turn it to adjust the instrument's volume comfortably.



Use Various Tips with a Universal Tipcone

A Universal Tipcone enhances the compatibility of the instrument and enables it to easily work with most of the internationally accepted standard tips.



Set the Volume with Perfection

A soft click sound at every increment ensures perfect volume setting and prevents any accidental changes. It also facilitates singlehanded operation.



Work with a Good Grip

A specially designed large Grippy provides good grip and great ease of use while operating.



Store Safely with a Holder

The Instrument includes a Holder that enables easy, efficient and safe storage.



Eject Tips wilh a Sequential Tip Ejector

A specially designed Sequential Tip Ejector and Tip Ejection Knob facilitate easy and effortless tip ejection, single-handedly.



Operate Flexibly

The lower housing of both the instruments can be rotated 360° providing enhanced operational flexibility.

Both 8-channel and 12-channel Micropipettes are offered in 6 models, covering volume ranges from 0.5-10 μ l to 40-300 μ l.

ORMATION	Model	Volume Range	lnc. μΙ	±%	λ ±μl	CV ±% ±µl	
SPECIFICATIONS AND ORDERING INFORMATION 8-channel Micropipette	RBO-MCA-8/10	0.5-10µl	0.02	1.6	0.16	1	0.1
	RBO-MCA-8/20	02-20µl	0.02	0.8	0.16	0.4	0.08
	RBO-MCA-8/50	5-50µl	0.1	0.8	0.4	0.4	0.2
	RBO-MCA-8/100	10-100µl	0.2	0.8	0.8	0.3	0.3
	RBO-MCA-8/200	20-200µl	0.2	0.8	1.6	0.3	0.6
	RBO-MCA-8/300	40-300µl	0.2	0.8	2.4	0.3	0.9

ORMATION	Model	Volume Range	lnc. μl	±%	Δ ±μl	±%	V ±μl
SPECIFICATIONS AND ORDERING INFORMATION 12-channel Micropipette	RBO-MCA-12/10	0.5-10µl	0.02	1.6	0.16	1	0.1
	RBO-MCA-12/20	02-20µl	0.02	0.8	0.16	0.4	0.08
	RBO-MCA-12/50	5-50µl	0.1	0.8	0.4	0.4	0.2
	RBO-MCA-12/100	10-100µl	0.2	0.8	0.8	0.3	0.3
	RBO-MCA-12/200	20-200µl	0.2	0.8	1.6	0.3	0.6
	RBO-MCA-12/300	40-300µl	0.2	0.8	2.4	0.3	0.9

Experience the Power of Precision During Routine Laboratory Operations

MICROLIT RBO is a range of High Precision Micropipettes that offer a sophisticated blend of features and functionality. Built by our in-house team of product design engineers, it is categorised into Single Channel (Fixed and Variable Volume) and Multichannel (8-channel and 12-channel) Micropipettes

These instruments are designed with ergonomics and intuitive handling in mind, and facilitate remarkable user experiences in practical laboratory environments.

Assured Quality with ISO 8655 Conformed Calibration



MICROLIT RBO is calibrated in an ISO 17025 accredited laboratory according to ISO 8655 standards.

A calibration certificate is included inside the product package.

A calibration tool is also included for quick in- lab re-calibration.

Colour Coding for Easy Identification



Colour-coding for different capacities facilitates easy identification during daily laboratory routine

Our Product Excellence





Our products reflect the design philosophy of our organization, combining the best performance parameters with the best user experience

We were honoured by CII Industrial Innovation Awards and adjudged a place in the top 25 Most Innovative Companies of 2021.

We are also accredited by a number of global organizations and have earned worldwide credibility.

MICROLIT

OUR REACH



YOUR SATISFACTION IS OUR PRIORITY

Microlit products follow GMP norms and are manufactured under comprehensive QA (Quality Assurance) & QC (Quality Control). Our products reflect the design philosophy of our organisation combining the best performance parameters with the best user experience. However, if you are dissatisfied with the operation of any of our products, get in touch with us or call your nearest Microlit dealer for free replacement.

CONTACT US

★ Microlit INDIA

629 Pakramau, Kursi Road, Lucknow 226026, India Phone: +91 9918625629, Email: info@microlit.com www.microlit.com

★ Microlit LATAM

Business Place Ibirapuera, 9th Floor, Number 93, Alameda dos Jurupis 1005 - Moema, Indianópolis São Paulo, Brasil CEP - 04088-000,

Phone: +55 11 93269-5932, Email: info-latam@microlit.com

★ Microlit USA

33 Wood Avenue South, Suite 600, Iselin, NJ 08830, USA Phone: +1 732 321 0852, Email: info-usa@microlit.com www.microlit.us

Follow us







