

MICROLITNERO®

Multi-functional Micropipette, Single Channel and Multichannel



ISO 9001




ISO 13485



ISO 17025

Unique Features of NERO® Single Channel (Fixed & Variable Volume) and Multi Channel Micropipette (8-Channel and 12-Channel)



Minimum dead air space

ACHIEVE PRECISION WITH μ Air® TECHNOLOGY

It ensures high precision by minimizing dead air space between piston and liquid in the tip.



SPRING AND BALL-BASED DIGIT CHANGE MECHANISM

It ensures no accidental volume change while carrying out various operations.



CALIBRATE EFFICIENTLY WITH PATENTED UniCal® TECHNOLOGY

It enables quick in-lab calibration in a single operation without traditional hit and trial method.



SEAMLESS INTEGRATED TIP EJECTOR

An in-built tip ejector ejects tips with optimal force and provides great aesthetic value.



SOFT PLUNGER MOVEMENT

Experience the lightest pipetting with 3-5N force for 1st step and 10-14N force for 2nd step.



EASY VOLUME ADJUSTMENT KNOB

It offers an extremely fast volume setting by effortless rotation of the plunger.



POLYCARBONATE HOUSING MATERIAL

It makes the micropipette durable, lightweight, scratch proof and dirt resistant.



ERGONOMIC LIGHTWEIGHT DESIGN

It facilitates single-handed and long duration of operation with ease.



UNIVERSAL TIP CONE

This makes the micropipette compatible with most of the internationally accepted standard tips.



FULLY AUTOCLAVABLE

This instrument is fully autoclavable at 121°C and 15 psi for a duration of 15-20 minutes.




Assured Quality with ISO 8655 Conformed Calibration

The India Design Mark 2021 awardee "NERO® micropipette" has been granted the patent for its unique calibration system, the UniCal® Technology that allows quick in-lab calibration in a single operation without disengaging the digits from the plunger mechanism. The Indian Patent Number is 405607.

How is UniCal® Technology Beneficial?

- ◆ It eliminates the inconvenience caused by the hit-and-trial method of calibration.
- ◆ It saves the cost and time of sending the instrument to another facility for third party calibration.
- ◆ It enables the user to re-calibrate without disassembling any component, disengaging the digits from the plunger or matching calibration markers on the micropipette to the volume adjustment chart in the user manual.



COLOUR CODING FOR EASY IDENTIFICATION

Variable Volume Micropipette



NRO-2

NRO-10

NRO-20

NRO-50

NRO-100

NRO-200

NRO-1000

NRO-5000

NRO-10000

Fixed Volume Micropipette



NRO-F-1, F-2, F-5

NRO-F-10

NRO-F-20, F-25

NRO-F-50

NRO-F-100

NRO-F-200

NRO-F-250, F-500, F-1000

NRO-F-2000, F-5000

NRO-F-10000

Specifications and Ordering Information Chart of NERO® High Precision Micropipette

	MODEL	VOLUME RANGE (μ l)	ACCURACY		CV	
			+/-%	+/- μ l	+/-%	+/- μ l
FIXED VOLUME MICROPIPETTE	NRO-F-1	1	5	0.05	5	0.05
	NRO-F-2	2	4	0.08	2	0.04
	NRO-F-5	5	2	0.10	1	0.05
	NRO-F-10	10	1	0.10	0.5	0.05
	NRO-F-20	20	0.8	0.16	0.4	0.08
	NRO-F-25	25	0.8	0.20	0.4	0.10
	NRO-F-50	50	0.8	0.40	0.4	0.20
	NRO-F-100	100	0.6	0.60	0.2	0.20
	NRO-F-200	200	0.6	1.20	0.2	0.40
	NRO-F-250	250	0.6	1.50	0.2	0.50
	NRO-F-500	500	0.6	3.00	0.2	1.00
	NRO-F-1000	1000	0.6	6.00	0.2	2.00
	NRO-F-2000	2000	0.6	12.00	0.2	4.00
	NRO-F-5000	5000	0.6	30.00	0.2	10.00
NRO-F-10000	10000	0.4	40.00	0.2	20.00	

	MODEL	VOLUME RANGE (μ l)	INC. (μ l)	ACCURACY		CV	
				+/-%	+/- μ l	+/-%	+/- μ l
VARIABLE VOLUME MICROPIPETTE	NRO-2.5	0.1-2.5	0.004	2	0.04	1.2	0.024
	NRO-10	0.5-10	0.01	1	0.10	0.5	0.05
	NRO-20	2-20	0.02	0.8	0.16	0.4	0.08
	NRO-50	5-50	0.04	0.8	0.40	0.4	0.20
	NRO-100	10-100	0.1	0.6	0.60	0.2	0.20
	NRO-200	20-200	0.2	0.6	1.20	0.2	0.40
	NRO-1000	100-1000	1.0	0.6	6.00	0.2	2.00
	NRO-5000	500-5000	4.0	0.6	30.00	0.2	10.00
	NRO-10000	1000-10000	10.0	0.6	60.00	0.2	20.00

	MODEL	VOLUME RANGE (μ l)	INC. (μ l)	ACCURACY		CV	
				+/-%	+/- μ l	+/-%	+/- μ l
8-CHANNEL MICROPIPETTE	NRO-E-10	0.5-10	0.01	1.6	0.16	1.00	0.01
	NRO-E-20	02-20	0.02	0.8	0.16	0.40	0.08
	NRO-E-50	05-50	0.04	0.8	0.40	0.40	0.20
	NRO-E-100	10-100	0.1	0.8	0.80	0.30	0.30
	NRO-E-200	20-200	0.2	0.8	1.60	0.30	0.60
	NRO-E-300	40-300	0.4	0.8	2.40	0.30	0.90

	MODEL	VOLUME RANGE (μ l)	INC. (μ l)	ACCURACY		CV	
				+/-%	+/- μ l	+/-%	+/- μ l
12-CHANNEL MICROPIPETTE	NRO-T-10	0.5-10	0.01	1.6	0.16	1.00	0.01
	NRO-T-20	02-20	0.02	0.8	0.16	0.40	0.08
	NRO-T-50	05-50	0.04	0.8	0.40	0.40	0.20
	NRO-T-100	10-100	0.1	0.8	0.80	0.30	0.30
	NRO-T-200	20-200	0.2	0.8	1.60	0.30	0.60
	NRO-T-300	40-300	0.4	0.8	2.40	0.30	0.90

The error limits (Accuracy and Coefficient of Variation) mentioned above are in accordance with DIN EN ISO 8655-2 and are based on the nominal capacity indicated on the instrument. MICROLIT NERO® is calibrated in an ISO 17025 accredited laboratory according to ISO 8655 standards and a Calibration Certificate is included in the product package.

A Complete Solution for all your Pipetting Needs

MICROLIT NERO® is a range of high precision micropipettes that offer a sophisticated blend of features and functionality. Built by our expert team of Product Design Engineers, it is available in Single Channel (Fixed and Variable Volume) and Multichannel (8-channel and 12-channel) Micropipettes.

These instruments are designed with ergonomics and intuitive handling in mind and facilitate remarkable user experience in practical laboratory environments.

Perform Re-calibration in your Laboratory with Unique Patented UniCal® Technology



MICROLIT NERO® is calibrated in an ISO 17025 accredited laboratory according to ISO 8655 standards.

A calibration certificate is included with each instrument.

The micropipette is designed with easy user calibration method and can be easily recalibrated in minimum steps.

Award-winning Design and Product Excellence



Microlit has been recognized for its innovation and leadership with several prestigious awards, including the **Japanese Good Design Award**, **CII Industrial Innovation Awards**, and a spot in the **Top 50 Most Innovative Companies of 2022**. This year, we proudly received the **Global Business Leadership Award** from **ET Now Leaders of Tomorrow 2025**, further solidifying our position as a global leader in Healthcare and Life Sciences Industry.



OUR REACH



YOUR SATISFACTION IS OUR PRIORITY

Established in 1991, Microlit is one of the world's leading manufacturers & exporters of laboratory liquid handling instruments. Our product range includes micropipettes, bottle top dispensers, electronic burette, electronic pipette filling device and other micropipette accessories. With our patented products, innovative technologies & unflinching trust of 8000+ consumers in 95+ countries, we are recognized as a respected & dependable brand in Healthcare and Lifesciences industry. Our offices are located in India (HQ), USA & Brazil. With a research-oriented & customer-centric team of product design engineers, our product design blends the best of functional performance & user experience. Our innovative products have helped us carve a niche in R&D industry while providing our users high level of precision & accuracy in their research work.

CONTACT US

Microlit INDIA

629 Pakramau, Kursi Road, Lucknow 226026, India
Phone: +91 9918625629, Email: info@microlit.com
www.microlit.com

Microlit USA

33 Wood Avenue South, Suite 600, Iselin, NJ 08830, USA
Phone: +1 732 321 0852, Email: info-usa@microlit.com
www.microlit.us

Microlit LATAM

Business Place Ibirapuera, 9th Floor, Number 93,
Alameda dos Jurupis 1005 - Moema,
Indianópolis São Paulo, Brasil CEP - 04088-000,
Phone: +55 11 93269-5932, Email: info-latam@microlit.com

Follow us

